

**Product:** RUBIN LOOK LED S SMOOTH 7500 PLX EDD IP44 34 830 / 620X620MM

**Index:** 19.4363.2413.34



## Description

Surface mounted luminaire equipped in highly efficient LED sources. Luminaire body made from steel sheet, powder coated.

## Product information

Category	Surface mounted luminaires
Family	RUBIN LOOK LED SMOOTH
Name	RUBIN LOOK LED S SMOOTH 7500 PLX EDD IP44 34 830 / 620X620MM
Index	19.4363.2413.34
EAN	5902107074128



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	7875
LED power [W]	39,8
Luminaire luminous flux [lm]	5924
Power of luminaire [W]	42,2
Luminaire's light efficiency [lm/W]	140,4
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Protection against electric shock	I
Protection degree	IP44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	8 (B10), 13 (B16), 13 (C10), 21 (C16)

**Mechanical data**



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	620 x 620 x 56

**A graph of light**

