

Product: RUBIN LOOK LED P SMOOTH 5400 PLX E IP44 21 840 / 600X600

Index: 19.4363.2821.21



Description

Surface mounted luminaire equipped in highly efficient LED sources. Luminaire body made from steel sheet, powder coated.

Product information

Category	Surface mounted luminaires
Family	RUBIN LOOK LED SMOOTH
Name	RUBIN LOOK LED P SMOOTH 5400 PLX E IP44 21 840 / 600X600
Index	19.4363.2821.21




Light and electrical data

Light source	LED
Luminous flux LED [lm]	6061
LED power [W]	30,6
Luminaire luminous flux [lm]	4559
Power of luminaire [W]	33,2
Luminaire's light efficiency [lm/W]	137,3
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Protection against electric shock	I
Protection degree	IP44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	12 (B10), 19 (B16), 20 (C10), 32 (C16)

Mechanical data

Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9006 (gray, metallic, fine structure)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	620 x 620 x 56



A graph of light

