

Product: RUBIN LOOK LED S SMOOTH 3750 PLX E IP44 34 840 / 620X365MM

Index: 19.4363.3221.34



Description

Surface mounted luminaire equipped in highly efficient LED sources. Luminaire body made from steel sheet, powder coated.

Product information

Category	Surface mounted luminaires
Family	RUBIN LOOK LED SMOOTH
Name	RUBIN LOOK LED S SMOOTH 3750 PLX E IP44 34 840 / 620X365MM
Index	19.4363.3221.34
EAN	5901867472281



Light and electrical data

Light source	LED
Luminous flux LED [lm]	3740
LED power [W]	23
Luminaire luminous flux [lm]	3223
Power of luminaire [W]	25
Luminaire's light efficiency [lm/W]	128,9
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Protection against electric shock	I
Protection degree	IP44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	54000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	15 (B10), 24 (B16), 24 (C10), 40 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	4,35
Dimensions [mm]	620 x 365 x 56

A graph of light

