

Product: RUBIN LOOK LED S SMOOTH 3750 PLX E IP44 34 840 / 620X365MM

Index: 19.4363.3221.34



Description

Surface mounted luminaire equipped in highly efficient LED sources. Luminaire body made from steel sheet, powder coated.

Product information


| | |
|----------|--|
| Category | Surface mounted luminaires |
| Family | RUBIN LOOK LED SMOOTH |
| Name | RUBIN LOOK LED S SMOOTH 3750 PLX E IP44 34 840 / 620X365MM |
| Index | 19.4363.3221.34 |
| EAN | 5901867472281 |



Light and electrical data

| | |
|-------------------------------------|--|
| Light source | LED |
| Luminous flux LED [lm] | 3740 |
| LED power [W] | 23 |
| Luminaire luminous flux [lm] | 3223 |
| Power of luminaire [W] | 25 |
| Luminaire's light efficiency [lm/W] | 128,9 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 109,6° / 109,6° |
| Protection against electric shock | I |
| Protection degree | IP44 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 54000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | standard on/off (E) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 15 (B10), 24 (B16), 24 (C10), 40 (C16) |

Mechanical data



| | |
|------------------|----------------------------|
| Assembly | surface mounted on ceiling |
| Material | steel sheet |
| Color | RAL 9016 (white) |
| Diffuser | PLX (PMMA opal) |
| Impact resistant | IK04 |
| Weight [kg] | 4,35 |
| Dimensions [mm] | 620 x 365 x 56 |

A graph of light

