

Product: METEOR V2 LED COMPACT 8000 PLX E 34 840 L-1203MM

Index: 19.4367.1321.34



## **Description**

Surface mounted luminaries equipped with highly efficient LED sources. Luminary base made from powder coated steel sheet. Luminaire diffuser made of polymethylmethacrylate in a smooth opal or microprismatic version. Luminary mounted directly on ceilings by raw plugs.

## **Product information**

Category	Compact
Family	METEOR V2 LED COMPACT
Name	METEOR V2 LED COMPACT 8000 PLX E 34 840 L-1203MM
Index	19.4367.1321.34
EAN	5902107452797















## Light and electrical data

Light source	LED
Luminous flux LED [lm]	8918
LED power [W]	44,4
Luminaire luminous flux [lm]	7331
Power of luminaire [W]	49,7
Luminaire's light efficiency [lm/W]	147,5
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 106° / 106,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	90000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	15 (B10), 25 (B16), 24 (C10), 38 (C16)



Mechanical data				
	Α			
	<b>エ</b> [			
В				

Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	1203 x 209 x 64

## A graph of light





