

Product: METEOR V2 LED COMPACT 3000 PLX E 04 840 L-620MM

Index: 19.4367.1521.04



Description

Surface mounted luminaries equipped with highly efficient LED sources. Luminary base made from powder coated steel sheet. Luminaire diffuser made of polymethylmethacrylate in a smooth opal or microprismatic version. Luminary mounted directly on ceilings by raw plugs.

Product information

Category	Compact
Family	METEOR V2 LED COMPACT
Name	METEOR V2 LED COMPACT 3000 PLX E 04 840 L-620MM
Index	19.4367.1521.04
EAN	5902107612634















Light and electrical data

Light source	LED
Luminous flux LED [lm]	3190,9
LED power [W]	17
Luminaire luminous flux [lm]	2512,5
Power of luminaire [W]	19
Luminaire's light efficiency [lm/W]	132,2
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 106° / 106,6°
Dhatabialagical riels along (IEC/EN	200
Photobiological risk class (IEC/EN 62471)	RG0
ŭ ,	I I
62471)	
62471) Protection against electric shock	1
Protection against electric shock Protection degree	I IP20
Protection against electric shock Protection degree Voltage	I IP20 220240 V, 5060 Hz
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h]	I IP20 220240 V, 5060 Hz 90000
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By	I IP20 220240 V, 5060 Hz 90000 L80/B10
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	I IP20 220240 V, 5060 Hz 90000 L80/B10 5 ÷ 30



Mechanical data				
А				
± [
В				

Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9005 (black)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	620 x 209 x 64

A graph of light







