

Product: METEOR V2 LED COMPACT 3000 PLX E 21 840 L-620MM

Index: 19.4367.1521.21



Description

Surface mounted luminaires equipped with highly efficient LED sources. Luminaire base made from powder coated steel sheet. Luminaire diffuser made of polymethylmethacrylate in a smooth opal or microprismatic version. Luminaire mounted directly on ceilings by raw plugs.

Product information


| | |
|----------|--|
| Category | Compact |
| Family | METEOR V2 LED COMPACT |
| Name | METEOR V2 LED COMPACT 3000 PLX E 21 840 L-620MM |
| Index | 19.4367.1521.21 |
| EAN | 5902107612559 |



Light and electrical data

| | |
|---|---|
| Light source | LED |
| Luminous flux LED [lm] | 3190,9 |
| LED power [W] | 17 |
| Luminaire luminous flux [lm] | 2512,5 |
| Power of luminaire [W] | 19 |
| Luminaire's light efficiency [lm/W] | 132,2 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 106° / 106,6° |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | I |
| Protection degree | IP20 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 90000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | standard on/off (E) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 23 (B10), 36 (B16), 35(C10), 60 (C16) |

Mechanical data



| | |
|------------------|----------------------------|
| Assembly | surface mounted on ceiling |
| Material | steel sheet |
| Color | RAL 9006 (grey) |
| Diffuser | PLX (PMMA opal) |
| Impact resistant | IK04 |
| Dimensions [mm] | 620 x 209 x 64 |

A graph of light

