

Product: METEOR V2 LED COMPACT 4000 PLX E 21 840 L-620MM

Index: 19.4367.1621.21



Description

Surface mounted luminaires equipped with highly efficient LED sources. Luminary base made from powder coated steel sheet. Luminaire diffuser made of polymethylmethacrylate in a smooth opal or micoprismatic version. Luminary mounted directly on ceilings by raw plugs.


Product information

Category	Compact
Family	METEOR V2 LED COMPACT
Name	METEOR V2 LED COMPACT 4000 PLX E 21 840 L-620MM
Index	19.4367.1621.21
EAN	5902107612719



Light and electrical data

Light source	LED
Luminous flux LED [lm]	4458,5
LED power [W]	22,2
Luminaire luminous flux [lm]	3809,1
Power of luminaire [W]	24,9
Luminaire's light efficiency [lm/W]	153
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 106° / 106,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	90000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)

Mechanical data

Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9006 (grey)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	620 x 209 x 64

A graph of light