

Product: METEOR V2 LED COMPACT 5000 PLX EDD 34 840 L-1460MM

Index: 19.4367.1723.34



## **Description**

Surface mounted luminaries equipped with highly efficient LED sources. Luminary base made from powder coated steel sheet. Luminaire diffuser made of polymethylmethacrylate in a smooth opal or microprismatic version. Luminary mounted directly on ceilings by raw plugs.

## **Product information**

Category	Compact
Family	METEOR V2 LED COMPACT
Name	METEOR V2 LED COMPACT 5000 PLX EDD 34 840 L-1460MM
Index	19.4367.1723.34
EAN	5902107613471















## Light and electrical data

Light source	LED		
Luminous flux LED [lm]	5575		
LED power [W]	28		
Luminaire luminous flux [lm]	4581,6		
Power of luminaire [W]	31,4		
Luminaire's light efficiency [lm/W]	145,9		
Color of the light [K]	4000		
CRI	>80		
SDCM (LED sources)	3		
Beam angle [°]	(C0-C180) / (C90-C270) - 106° / 106,6°		
Photobiological risk class (IEC/EN 62471)	RG0		
Drotaction against aleatric shook			
Protection against electric shock	I		
Protection degree	I IP20		
	•		
Protection degree	IP20		
Protection degree Voltage	IP20 220240 V, 5060 Hz		
Protection degree  Voltage  Lifetime of LED sources [h]	IP20 220240 V, 5060 Hz 90000		
Protection degree  Voltage  Lifetime of LED sources [h]  Lx/By	IP20 220240 V, 5060 Hz 90000 L80/B10		
Protection degree  Voltage  Lifetime of LED sources [h]  Lx/By  Operating temperature range [°C]	IP20 220240 V, 5060 Hz 90000 L80/B10 5 ÷ 30		



Mechanical data			
	A		
	<b>エ</b> [	,	
В			

Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	1460 x 209 x 64

## A graph of light





