

Product: METEOR V2 LED COMPACT 7000 PLX EDD 21 830 L-1460MM

Index: 19.4367.1813.21



## **Description**

Surface mounted luminaries equipped with highly efficient LED sources. Luminary base made from powder coated steel sheet. Luminaire diffuser made of polymethylmethacrylate in a smooth opal or microprismatic version. Luminary mounted directly on ceilings by raw plugs.

## **Product information**

Category	Compact
Family	METEOR V2 LED COMPACT
Name	METEOR V2 LED COMPACT 7000 PLX EDD 21 830 L-1460MM
Index	19.4367.1813.21
EAN	5902107613860















## Light and electrical data

Light source	LED
Luminous flux LED [lm]	7475
LED power [W]	42,5
Luminaire luminous flux [lm]	5687,4
Power of luminaire [W]	47,6
Luminaire's light efficiency [lm/W]	119,5
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 106° / 106,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	90000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	14 (B10), 23 (B16), 22 (C10), 35 (C16)



Mechanical data				
Α				
•				
工				
B				

Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9006 (grey)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	1460 x 209 x 64

## A graph of light







