

**Product:** METEOR V2 LED COMPACT 7000 PLX E 04 840 L-1460MM

**Index:** 19.4367.1821.04



## Description

Surface mounted luminaires equipped with highly efficient LED sources. Luminaire base made from powder coated steel sheet. Luminaire diffuser made of polymethylmethacrylate in a smooth opal or microprismatic version. Luminaire mounted directly on ceilings by raw plugs.

## Product information

|          |  |
|----------|--|
| Category | Compact  |
| Family   | METEOR V2 LED COMPACT                            |
| Name     | METEOR V2 LED COMPACT 7000 PLX E 04 840 L-1460MM |
| Index    | 19.4367.1821.04                                  |



## Light and electrical data

|                                     |  |
|-------------------------------------|--|
| Light source                        | LED                                    |
| Luminous flux LED [lm]              | 7206                                   |
| LED power [W]                       | 37,5                                   |
| Luminaire luminous flux [lm]        | 5923,3                                 |
| Power of luminaire [W]              | 42                                     |
| Luminaire's light efficiency [lm/W] | 141                                    |
| Color of the light [K]              | 4000                                   |
| CRI                                 | >80                                    |
| SDCM (LED sources)                  | 3                                      |
| Beam angle [°]                      | (C0-C180) / (C90-C270) - 106° / 106°   |
| Protection against electric shock   | I                                      |
| Protection degree                   | IP20                                   |
| Voltage                             | 220..240 V, 50..60 Hz                  |
| Lifetime of LED sources [h]         | 90000                                  |
| Lx/By                               | L80/B10                                |
| Operating temperature range [°C]    | 5 ÷ 35                                 |
| Driver                              | standard on/off (E)                    |
| Power factor cos φ                  | >0,95                                  |
| Circuit load capacity               | 11 (B10), 19 (B16), 19 (C10), 31 (C16) |

## Mechanical data



|                  |                            |
|------------------|----------------------------|
| Assembly         | surface mounted on ceiling |
| Material         | steel sheet                |
| Color            | RAL 9005 (black)           |
| Diffuser         | PLX (PMMA opal)            |
| Impact resistant | IK04                       |
| Dimensions [mm]  | 1460 x 209 x 64            |

## A graph of light

