

Product: METEOR V2 LED COMPACT 2600 MICRO-PRM E 21 830 L-1203MM

Index: 19.4367.2411.21



Description

Surface mounted luminaries equipped with highly efficient LED sources. Luminary base made from powder coated steel sheet. Luminaire diffuser made of polymethylmethacrylate in a smooth opal or microprismatic version. Luminary mounted directly on ceilings by raw plugs.

Product information

Category Compact **METEOR V2 LED COMPACT** Family Name METEOR V2 LED COMPACT 2600 MICRO-PRM E 21 830 L-1203MM Index















Light and electrical data

Light source	LED
Luminous flux LED [lm]	2524
LED power [W]	12,8
Luminaire luminous flux [lm]	2336,4
Power of luminaire [W]	15,1
Luminaire's light efficiency [lm/W]	154,7
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 84,2° / 91,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	90000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	46 (B10), 74 (B16), 72 (C10), 115 (C16)



Mechanical data	
A	
= [
В	

Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9006 (grey)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	1203 x 209 x 64

A graph of light







