

**Product:** METEOR V2 LED COMPACT 4000 MICRO-PRM E 04 840 L-620MM

**Index:** 19.4367.2621.04



### Description

Surface mounted luminaries equipped with highly efficient LED sources. Luminary base made from powder coated steel sheet. Luminaire diffuser made of polymethylmethacrylate in a smooth opal or microprismatic version. Luminary mounted directly on ceilings by raw plugs.

### Product information


|          |   |
|----------|---|
| Category | Compact   |
| Family   | METEOR V2 LED COMPACT                                 |
| Name     | METEOR V2 LED COMPACT 4000 MICRO-PRM E 04 840 L-620MM |
| Index    | 19.4367.2621.04                                       |



### Light and electrical data

|                                     |  |
|-------------------------------------|--|
| Light source                        | LED                                    |
| Luminous flux LED [lm]              | 4634                                   |
| LED power [W]                       | 24                                     |
| Luminaire luminous flux [lm]        | 3934,3                                 |
| Power of luminaire [W]              | 26,9                                   |
| Luminaire's light efficiency [lm/W] | 146,3                                  |
| Color of the light [K]              | 4000                                   |
| CRI                                 | >80                                    |
| SDCM (LED sources)                  | 3                                      |
| Beam angle [°]                      | (C0-C180) / (C90-C270) - 84,2° / 91,4° |
| Protection against electric shock   | I                                      |
| Protection degree                   | IP20                                   |
| Voltage                             | 220..240 V, 50..60 Hz                  |
| Lifetime of LED sources [h]         | 90000                                  |
| Lx/By                               | L80/B10                                |
| Operating temperature range [°C]    | 5 ÷ 35                                 |
| Driver                              | standard on/off (E)                    |
| Power factor cos φ                  | >0,95                                  |
| Circuit load capacity               | 25 (B10), 40 (B16), 39 (C10), 62 (C16) |

### Mechanical data



|                  |   |
|------------------|---|
| Assembly         | surface mounted on ceiling                |
| Material         | steel sheet                               |
| Color            | RAL 9005 (black)                          |
| Diffuser         | Micro-PRM (micro-prismatic diffuser PMMA) |
| Impact resistant | IK04                                      |
| Dimensions [mm]  | 620 x 209 x 64                            |

A graph of light

