

Product: METEOR V2 LED COMPACT 7000 MICRO-PRM EDD 34 830 L-1460MM

Index: 19.4367.2813.34



Description

Surface mounted luminaries equipped with highly efficient LED sources. Luminary base made from powder coated steel sheet. Luminaire diffuser made of polymethylmethacrylate in a smooth opal or microprismatic version. Luminary mounted directly on ceilings by raw plugs.

Product information

Category	Compact	
Family	METEOR V2 LED COMPACT	
Name	METEOR V2 LED COMPACT 7000 MICRO-PRM EDD 34 830 L- 1460MM	
Index	19.4367.2813.34	
EAN	5902107613587	















Light and electrical data

Light source	LED
Luminous flux LED [lm]	7475
LED power [W]	42,5
Luminaire luminous flux [lm]	5874,2
Power of luminaire [W]	47,6
Luminaire's light efficiency [lm/W]	123,4
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 84,2° / 91,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	90000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	14 (B10), 23 (B16), 22 (C10), 35 (C16)



Mechanical data		
A		
± Ţ		
В		

Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	1460 x 209 x 64

A graph of light







