

Product: BONANOVA 24000 WIDE EDD IP66 22 857

Index: 19.4369.4263.22



Description

Innovative industrial luminaire with versatile installation options. Sleek housing without external heatsinks. The ingenious design prevents dust and dirt buildup, for optimum performance and extended component lifespan.

Product information



Category	Industrial luminaires
Family	BONANOVA
Name	BONANOVA 24000 WIDE EDD IP66 22 857
Index	19.4369.4263.22
EAN	5902107566180



Light and electrical data

Light source	LED
Luminous flux LED [lm]	25588
LED power [W]	140,9
Luminaire luminous flux [lm]	22108
Power of luminaire [W]	157,8
Luminaire's light efficiency [lm/W]	140,1
Color of the light [K]	5700
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 98,6° / 98,4°
Protection against electric shock	I
Protection degree	IP66
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	-40 ÷ 35
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	5 (B10), 8 (B16), 8 (C10), 13 (C16)

Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9007 (dark grey)
Diffuser	hardened transparent glass
Impact resistant	IK09
Dimensions [mm]	Ø480 x 177

A graph of light

