

Product: BONANOVA 16000 MEDIUM EDD IP66 22 857

Index: 19.4369.2163.22



Description

Innovative industrial luminaire with versatile installation options. Sleek housing without external heatsinks. The ingenious design prevents dust and dirt buildup, for optimum performance and extended component lifespan.

Product information

| | |
|----------|---------------------------------------|
| Category | Industrial luminaires |
| Family | BONANOVA |
| Name | BONANOVA 16000 MEDIUM EDD IP66 22 857 |
| Index | 19.4369.2163.22 |



Light and electrical data

| | |
|-------------------------------------|--|
| Light source | LED |
| Luminous flux LED [lm] | 17688 |
| LED power [W] | 90,6 |
| Luminaire luminous flux [lm] | 15247,1 |
| Power of luminaire [W] | 101,5 |
| Luminaire's light efficiency [lm/W] | 150,2 |
| Color of the light [K] | 5700 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 69,4° / 69,2° |
| Protection against electric shock | I |
| Protection degree | IP66 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 100000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | -40 ÷ 35 |
| Driver | DIM DALI (EDD) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 6 (B10), 10 (B16), 10 (C10), 17 (C16) |

Mechanical data



| | |
|------------------|----------------------------|
| Assembly | surface mounted on slings |
| Material | aluminum |
| Color | RAL 9007 (dark gray) |
| Diffuser | hardened transparent glass |
| Impact resistant | IK09 |
| Dimensions [mm] | Ø480 x 177 |

A graph of light

