

**Product:** BONANOVA 16000 ULTRA-WIDE E IP66 22 830

**Index:** 19.4369.2311.22



## Description

Innovative industrial luminaire with versatile installation options. Sleek housing without external heatsinks. The ingenious design prevents dust and dirt buildup, for optimum performance and extended component lifespan.

## Product information

Category	Industrial luminaires
Family	BONANOVA
Name	BONANOVA 16000 ULTRA-WIDE E IP66 22 830
Index	19.4369.2311.22
EAN	5902107565534



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	17016
LED power [W]	90,6
Luminaire luminous flux [lm]	15824,9
Power of luminaire [W]	101,5
Luminaire's light efficiency [lm/W]	155,9
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 115,4° / 117,8°
Protection against electric shock	I
Protection degree	IP66
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	-40 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	6 (B10), 10 (B16), 10 (C10), 17 (C16)

## Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9007 (dark grey)
Diffuser	hardened transparent glass
Impact resistant	IK09
Dimensions [mm]	Ø480 x 177

A graph of light

