

**Product:** BONANOVA 20000 MEDIUM EDD IP66 22 857

**Index:** 19.4369.3163.22



## Description

Innovative industrial luminaire with versatile installation options. Sleek housing without external heatsinks. The ingenious design prevents dust and dirt buildup, for optimum performance and extended component lifespan.

## Product information

Category	<b>Industrial luminaires</b>
Family	<b>BONANOVA</b>
Name	<b>BONANOVA 20000 MEDIUM EDD IP66 22 857</b>
Index	<b>19.4369.3163.22</b>
EAN	<b>5902107566142</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>22296</b>
LED power [W]	<b>119</b>
Luminaire luminous flux [lm]	<b>19219,2</b>
Power of luminaire [W]	<b>133,3</b>
Luminaire's light efficiency [lm/W]	<b>144,2</b>
Color of the light [K]	<b>5700</b>
CRI	<b>&gt;80</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 69,4° / 69,2°</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP66</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>100000</b>
Lx/By	<b>L80/B10</b>
Operating temperature range [°C]	<b>-40 ÷ 35</b>
Driver	<b>DIM DALI (EDD)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>5 (B10), 8 (B16), 8 (C10), 13 (C16)</b>

**Mechanical data**



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9007 (dark grey)
Diffuser	hardened transparent glass
Impact resistant	IK09
Dimensions [mm]	Ø480 x 177

**A graph of light**

