

Product: BONANOVA 20000 WIDE E IP66 22 857

Index: 19.4369.3261.22



Description

Innovative industrial luminaire with versatile installation options. Sleek housing without external heatsinks. The ingenious design prevents dust and dirt buildup, for optimum performance and extended component lifespan.

Product information

| | |
|----------|--|
| Category | Industrial luminaires |
| Family | BONANOVA |
| Name | BONANOVA 20000 WIDE E IP66 22 857 |
| Index | 19.4369.3261.22 |



Light and electrical data

| | |
|-------------------------------------|---|
| Light source | LED |
| Luminous flux LED [lm] | 22296 |
| LED power [W] | 119 |
| Luminaire luminous flux [lm] | 19263,7 |
| Power of luminaire [W] | 133,3 |
| Luminaire's light efficiency [lm/W] | 144,5 |
| Color of the light [K] | 5700 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 98,6° / 98,4° |
| Protection against electric shock | I |
| Protection degree | IP66 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 100000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | -40 ÷ 35 |
| Driver | standard on/off (E) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 5 (B10), 8 (B16), 8 (C10), 13 (C16) |

Mechanical data



| | |
|------------------|-----------------------------------|
| Assembly | surface mounted on slings |
| Material | aluminum |
| Color | RAL 9007 (dark gray) |
| Diffuser | hardened transparent glass |
| Impact resistant | IK09 |
| Dimensions [mm] | Ø480 x 177 |

A graph of light

