

Product: BONANOVA 20000 ULTRA-WIDE EDD IP66 22 857

Index: 19.4369.3363.22



Description

Innovative industrial luminaire with versatile installation options. Sleek housing without external heatsinks. The ingenious design prevents dust and dirt buildup, for optimum performance and extended component lifespan.

Product information

Category	Industrial luminaires
Family	BONANOVA
Name	BONANOVA 20000 ULTRA-WIDE EDD IP66 22 857
Index	19.4369.3363.22



Light and electrical data

Light source	LED
Luminous flux LED [lm]	22296
LED power [W]	119
Luminaire luminous flux [lm]	20735,3
Power of luminaire [W]	133,3
Luminaire's light efficiency [lm/W]	155,6
Color of the light [K]	5700
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 115,4° / 117,8°
Protection against electric shock	I
Protection degree	IP66
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	-40 ÷ 35
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	5 (B10), 8 (B16), 8 (C10), 13 (C16)

Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9007 (dark gray)
Diffuser	hardened transparent glass
Impact resistant	IK09
Dimensions [mm]	Ø480 x 177

A graph of light

