

Product: LUXCAN ZOOM 5500 20-60° E 04 927 3F

Index: 19.4370.5171.04



Description

Projector incorporates an ingenious system that allows varying the beam angle with a smooth movement of the front ring. With this simple gesture you can adjust the angle between 20 and 60°. Its great advantage is that instead of selecting a fixed lens and having to change the projectors, or change the lens of those already installed, this function allows the customer to modify the light beam to adapt to the project needs at any moment. Projector housing made of die-cast aluminium. Swivel angle 350°, tilt angle 90°. Low flicker power supply. High luminous efficiency of the luminaire.


Product information

Category	Projectors
Family	LUXCAN ZOOM
Name	LUXCAN ZOOM 5500 20-60° E 04 927 3F
Index	19.4370.5171.04
EAN	5902107572310



Light and electrical data

Light source	LED
Luminous flux LED [lm]	4483,5
LED power [W]	35,1
Luminaire luminous flux [lm]	3766/4012/4138 (20/40/60°)
Power of luminaire [W]	41,3
Luminaire's light efficiency [lm/W]	91,2/97,2/100,2 (20/40/60°)
Color of the light [K]	2700
CRI	>90
SDCM (LED sources)	3
Beam angle [°]	20°-60°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	II
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	15 (B10), 25 (B16), 25 (C10), 40 (C16)

Mechanical data

Assembly	mounted on a three-phase track
Material	aluminum
Color	RAL 9005 (black)
Diffuser	optical system based on PMMA lenses
Impact resistant	IK04
Dimensions [mm]	Ø80 x 185

