

**Product: GRANVIA 7500 WIDE E 34 840 / L-900MM** 

Index: 19.4377.8H21.34



## **Description**

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 lm/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

## **Product information**

| Category | Industrial luminaires                |
|----------|--------------------------------------|
| Family   | GRANVIA                              |
| Name     | GRANVIA 7500 WIDE E 34 840 / L-900MM |
| Index    | 19.4377.8H21.34                      |
| EAN      | 5902107656690                        |















## Light and electrical data

| Light source                              | LED                                    |  |
|---|--|--|
| Luminous flux LED [lm]                    | 7672,8                                 |  |
| LED power [W]                             | 37,6                                   |  |
| Luminaire luminous flux [lm]              | 7375,7                                 |  |
| Power of luminaire [W]                    | 42,1                                   |  |
| Luminaire's light efficiency [lm/W]       | 175,2                                  |  |
| Color of the light [K]                    | 4000                                   |  |
| CRI                                       | >80                                    |  |
| SDCM (LED sources)                        | 3                                      |  |
| Beam angle [°]                            | (C0-C180) / (C90-C270) - 86,2° / 84,4° |  |
| Photobiological risk class (IEC/EN 62471) | RG0                                    |  |
| Protection against electric shock         | I                                      |  |
| Protection degree                         | IP20                                   |  |
| Voltage                                   | 220240 V, 5060 Hz                      |  |
| Lifetime of LED sources [h]               | 90000                                  |  |
| Lx/By                                     | L80/B10                                |  |
| Operating temperature range [°C]          | -20 ÷ 35                               |  |
| Driver                                    | standard on/off (E)                    |  |
| Power factor cos φ                        | >0,95                                  |  |
| Circuit load capacity                     | 16 (B10), 26 (B16), 23 (C10), 37 (C16) |  |



| Mechanical data | Assembly         | directly mounted to ceiling construction or<br>surface mounted on slings |
|-----------------|------------------|--|
| В               | Material         | steel sheet  |
|                 | Color            | RAL 9016 (white)   |
|                 | Diffuser         | optical system based on PMMA lenses                                      |
|                 | Impact resistant | IK06   |
| A               | Dimensions [mm]  | 900 x 72 x 66  |

## A graph of light

