

Product: GRANVIA 10500 ASY E 34 840 / L-2250MM

Index: 19.4377.1821.34



## **Description**

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 lm/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

## **Product information**

Category	Industrial luminaires
Family	GRANVIA
Name	GRANVIA 10500 ASY E 34 840 / L-2250MM
Index	19.4377.1821.34
EAN	5902107593827















## Light and electrical data

Light source	LED
Luminous flux LED [lm]	10817,6
LED power [W]	50,1
Luminaire luminous flux [lm]	10184,5
Power of luminaire [W]	56,1
Luminaire's light efficiency [lm/W]	181,5
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	asymmetric light distribution
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	90000
Lx/By	L80/B10
Operating temperature range [°C]	-20 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	11 (B10), 17 (B16), 16 (C10), 27 (C16)



Mechanical data	Assembly	directly mounted to ceiling construction or surface mounted on slings
В	Material	steel sheet
<b>⊢</b>	Color	RAL 9016 (white)
	Diffuser	optical system based on PMMA lenses
^	Impact resistant	IK06
Α	Dimensions [mm]	2250 x 72 x 66

## A graph of light

