

Product: GRANVIA 6000 DOUBLE-ASY EDD 34 840 / L-900MM

Index: 19.4377.2G23.34



## Description

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 lm/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.


## Product information

Category	Industrial luminaires
Family	GRANVIA
Name	GRANVIA 6000 DOUBLE-ASY EDD 34 840 / L-900MM
Index	19.4377.2G23.34
EAN	5902107656140



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	6392
LED power [W]	30,5
Luminaire luminous flux [lm]	6120,4
Power of luminaire [W]	34,2
Luminaire's light efficiency [lm/W]	179
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 79,4° / 109,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	90000
Lx/By	L80/B10
Operating temperature range [°C]	-20 ÷ 35
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)

**Mechanical data**

Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	optical system based on PMMA lenses
Impact resistant	IK06
Dimensions [mm]	900 x 72 x 66

**A graph of light**