

Product: GRANVIA 8500 DOUBLE-ASY-WIDE E 34 830 / L-2250MM Index: 19.4377.3711.34



Description

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 Im/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

>0,95

11 (B10), 17 (B16), 16 (C10), 27 (C16)

Product information				
	Category	y Industrial luminaires		
	Family	GRANVIA		
	Name	ame GRANVIA 8500 DOUBLE-ASY-WIDE E 34 830 / L-2250MM		
	Index	19.4377.3711.34		
	EAN	5902107596774		
		$\overbrace{ED} \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus_{n \text{ for } n \text$	Ð	
Light and electrical data	Light sour	urce LED		
	Luminous	IS flux LED [Im] 8311,3		
	LED powe	ver [W] 39,6		
	Luminaire	re luminous flux [lm] 7631,5		
	Power of I	f luminaire [W] 44,4		
	Luminaire	re's light efficiency [lm/W] 171,9		
	Color of th	the light [K] 3000		
	CRI	>80		
	SDCM (LE	_ED sources) 3		
	Beam ang	ngle [°] (C0-C180) / (C90-C270) - 95,4° / 101,8°		
	Photobiolo 62471)	ological risk class (IEC/EN RG0		
	Protection	on against electric shock I		
	Protection	on degree IP20		
	Voltage	220240 V, 5060 Hz		
	Lifetime of	of LED sources [h] 90000		
	Lx/By	L80/B10		
	Operating	g temperature range [°C] -20 ÷ 35		
	Driver	standard on/off (E)		

Power factor $\cos \varphi$

Circuit load capacity

Mechanical data Assembly directly mounted to ceiling construction or surface mounted on slings **□ ±**] Material steel sheet В Color RAL 9016 (white) optical system based on PMMA lenses Diffuser IK06 Impact resistant А Dimensions [mm] 2250 x 72 x 66

A graph of light

