

Product: GRANVIA 10500 DOUBLE-ASY-WIDE EDD 34 840 / L-2250MM Index: 19.4377.3823.34




Description

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 Im/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

| Product information | | Category Industrial luminaires | | |
|---------------------------|--|--------------------------------|-----------------------------|--|
| | | | GRANVIA | |
| | | Family | | |
| | | Name | | IBLE-ASY-WIDE EDD 34 840 / L-2250MM |
| | | Index | 19.4377.3823.34 | |
| | | | | |
| Light and electrical data | | Light sour | rce | LED |
| | | Luminous | s flux LED [lm] | 10817,6 |
| | | LED powe | er [W] | 50,1 |
| | | Luminaire | e luminous flux [lm] | 9932,7 |
| | | Power of | luminaire [W] | 56,1 |
| | | Luminaire | e's light efficiency [lm/W] | 177,1 |
| | | Color of the | he light [K] | 4000 |
| | | CRI | | >80 |
| | | SDCM (LI | ED sources) | 3 |
| | | Beam ang | gle [°] | (C0-C180) / (C90-C270) - 95,4° / 101,8° |
| | | Photobiol 62471) | ogical risk class (IEC/EN | RG0 |
| | | Protection | n against electric shock | I |
| | | Protection | n degree | IP20 |
| | | Voltage | | 220240 V, 5060 Hz |
| | | Lifetime o | of LED sources [h] | 90000 |
| | | Lx/By | | L80/B10 |
| | | Operating | g temperature range [°C] | -20 ÷ 35 |
| | | Driver | | DIM DALI (EDD) |
| | | Power fac | ctor cos φ | >0,95 |
| | | Circuit loa | ad capacity | 14 (B10), 23 (B16), 22 (C10), 35 (C16 |

Mechanical data Assembly directly mounted to ceiling construction or surface mounted on slings **□ ±**] Material steel sheet В Color RAL 9016 (white) optical system based on PMMA lenses Diffuser IK06 Impact resistant А Dimensions [mm] 2250 x 72 x 66

A graph of light



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 02-06-2025