


Product: GRANVIA PRO 17500 MEDIUM E 34 840 / L-1500MM Index: 19.4378.4721.34



Description


A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 lm/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

(C16)

Product information		Category Industrial luminaires					
		Family	GRANVIA PRO				
		Name GRANVIA PRO 17500 MEDIUM E 34 840 / L-1500MM					
		Index	19.4378.4721.34				
		EAN	5902107600525				
Light and electrical data		Light source	e		LED		
		Luminous flux LED [lm]			17891,1		
		LED power [W]			92,8		
		Luminaire luminous flux [lm]			17332,2		
		Power of luminaire [W]			104		
		Luminaire's light efficiency [lm/W]			166,7		
		Color of the light [K]			4000		
		CRI			>80		
		SDCM (LED sources)			3		
		Beam angle [°]			(C0-C180) / (C90-C270) - 61,2° / 61,4°		
		Photobiological risk class (IEC/EN 62471)			RG0		
		Protection against electric shock			I		
		Protection degree			IP20		
		Voltage			220240 V, 5060 Hz		
		Lifetime of LED sources [h]			100000		
		Lx/By			L80/B10		
		Operating temperature range [°C]			-20 ÷ 35		
		Driver			standard on/off (E)		
		Power factor $\cos \phi$			>0,95		
		Circuit load capacity			10 (B10), 16 (B16), 16 (C10), 32		

Mechanical data Assembly directly mounted to ceiling construction or surface mounted on slings **□ ±**] Material steel sheet В Color RAL 9016 (white) optical system based on PMMA lenses Diffuser IK06 Impact resistant А Dimensions [mm] 1500 x 72 x 66

A graph of light



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025