

Product: GRANVIA PRO 13000 ULTRA-WIDE E 34 840 / L-1500MM

Index: 19.4378.7521.34



## **Description**

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 lm/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

## **Product information**

Category	Industrial luminaires
Family	GRANVIA PRO
Name	GRANVIA PRO 13000 ULTRA-WIDE E 34 840 / L-1500MM
Index	19.4378.7521.34
EAN	5902107599614















## Light and electrical data

	. ==
Light source	LED
Luminous flux LED [lm]	13005,4
LED power [W]	62,5
Luminaire luminous flux [lm]	12542,2
Power of luminaire [W]	70
Luminaire's light efficiency [lm/W]	179,2
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 125,6° / 121,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection against electric shock Protection degree	I IP20
	•
Protection degree	IP20
Protection degree Voltage	IP20 220240 V, 5060 Hz
Protection degree  Voltage  Lifetime of LED sources [h]	IP20 220240 V, 5060 Hz 100000
Protection degree  Voltage  Lifetime of LED sources [h]  Lx/By	IP20 220240 V, 5060 Hz 100000 L80/B10
Protection degree  Voltage  Lifetime of LED sources [h]  Lx/By  Operating temperature range [°C]	IP20 220240 V, 5060 Hz 100000 L80/B10 -20 ÷ 35



Mechanical data	Assembly	directly mounted to ceiling construction or surface mounted on slings
В	Material	steel sheet
<b>⊢</b>	Color	RAL 9016 (white)
	Diffuser	optical system based on PMMA lenses
	Impact resistant	IK06
A	Dimensions [mm]	1500 x 72 x 66

## A graph of light

