

Product: GRANVIA PRO 15000 ASY EDD 34 840 / L-2250MM Index: 19.4378.1C23.34



Description

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 Im/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

Product i	information
-----------	-------------


Category	Industrial Iuminaires	
Family	GRANVIA PRO	
Name	GRANVIA PRO 15000 ASY EDD 34 840 / L-2250MM	
Index	19.4378.1C23.34	
EAN	5902107599829	
	$\overbrace{LED} (\overbrace{ED}) (\mathsf{$	

Light and electrical data

Light source	LED
Luminous flux LED [lm]	15143,8
LED power [W]	71,1
Luminaire luminous flux [lm]	14257,5
Power of luminaire [W]	79,7
Luminaire's light efficiency [lm/W]	178,9
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	asymmetric light distribution
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	-20 ÷ 35
Driver	DIM DALI (EDD)
Power factor $\cos \phi$	>0,95
Circuit load capacity	14 (B10), 23 (B16), 22 (C10), 35 (C16)

Mechanical data Assembly directly mounted to ceiling construction or surface mounted on slings **□ ±**] Material steel sheet В Color RAL 9016 (white) optical system based on PMMA lenses Diffuser IK06 Impact resistant А Dimensions [mm] 2250 x 72 x 66

A graph of light



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025