

Product: GRANVIA PRO 7500 DOUBLE-ASY EDD 34 830 / L-900MM Index: 19.4378.2L13.34



Description

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 Im/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

Product information	Category Industrial luminaires Family GRANVIA PRO Name GRANVIA PRO 7500 DOUBLE-ASY EDD 34 830 / L-900MM Index 19.4378.2L13.34 EAN 5902107658489 Image: Comparison of the product of
Light and electrical data	Light sourceLEDLuminous flux LED [Im]7413,1LED power [W]37,5Luminaire luminous flux [Im]7098,1Power of luminaire [W]42Luminaire's light efficiency [Im/W]169Color of the light [K]3000CRI>80
	SDCM (LED sources) 3 Beam angle [°] (C0-C180) / (C90-C270) - 79,4° / 109,2°
	Photobiological risk class (IEC/EN RG0 62471)
	Protection against electric shock
	Protection degree IP20
	Voltage 220240 V, 5060 Hz
	Lifetime of LED sources [h] 100000
	Lx/By L80/B10
	Operating temperature range [°C] -20 ÷ 35
	Driver DIM DALI (EDD)
	Power factor cos φ >0,95
	Circuit load capacity 14 (B10), 23 (B16), 22 (C10), 35 (C10)

Mechanical data Assembly directly mounted to ceiling construction or surface mounted on slings **□ ±**] Material steel sheet В Color RAL 9016 (white) optical system based on PMMA lenses Diffuser IK06 Impact resistant А Dimensions [mm] 900 x 72 x 66

A graph of light

