


Product: GRANVIA PRO 10500 DOUBLE-ASY E 34 840 / L-900MM Index: 19.4378.2N21.34



Description

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 Im/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

	Ostavas		
Product information	Category		
	Family	GRANVIA PRO	
	Name		OOUBLE-ASY E 34 840 / L-900MM
	Index	19.4378.2N21.34	
	EAN	5902107659110	
Light and electrical data	Light sou	rce	LED
	Luminou	s flux LED [lm]	10734,7
	LED pow	er [W]	54,6
	Luminair	e luminou <mark>s flux [lm]</mark>	10278,5
	Power of	luminaire [W]	61,1
	Luminair	e's light efficiency [lm/W]	168,2
	Color of	he light [K]	4000
	CRI		>80
	SDCM (L	ED sources)	3
	Beam an	gle [°]	(C0-C180) / (C90-C270) - 79,4° / 109,2°
	Photobio 62471)	logical risk class (IEC/EN	RG0
	Protectio	n against electric shock	I
	Protectio	n degree	IP20
	Voltage		220240 V, 5060 Hz
	Lifetime	of LED sources [h]	100000
	Lx/By		L80/B10
	Operatin	g temperature range [°C]	-20 ÷ 35
	Driver		standard on/off (E)
	Power fa	ctor cos φ	>0,95
	Circuit lo	ad capacity	10 (B10), 16 (B16), 16 (C10), 32 (C16)

Mechanical data Assembly directly mounted to ceiling construction or surface mounted on slings **□ ±**] Material steel sheet В Color RAL 9016 (white) optical system based on PMMA lenses Diffuser IK06 Impact resistant А Dimensions [mm] 900 x 72 x 66

A graph of light

