

Product: GRANVIA PRO 12000 DOUBLE-ASY E 34 830 / L-900MM Index: 19.4378.2011.34



Description

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 Im/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

Product information	Cate	Category Industrial luminaires							
	Fam	ily	GRANVIA PRO						
	Nam	me GRANVIA PRO 12000 DOUBLE-ASY E 34 830 / L-90					0MM	ОММ	
	Inde	х	19 <mark>.4378.2</mark> 011.34						
	EAN		5902107659424						
				E		IK ₆	Indoor		
Light and electrical data	Ligh	t source	2	L	ED				
	Lum	inous flu	ux LED [lm]	1	1701,2				
		LED power [W]			64,7				
	Lum	Luminaire luminous flux [lm]			11204				
	Pow	er of lur	ninaire [W]	7	2,5				
	Lum	Luminaire's light efficiency [lm/W] Color of the light [K] CRI SDCM (LED sources)			154,5 3000 >80 3				
	Colo								
	CRI								
	SDC								
	Bear	Beam angle [°]			(C0-C180) / (C90-C270) - 79,4° / 109,2°				
	Phot 624		ical risk class (IEC/EN	R	G0				
	Prot	Protection against electric shock		I	I				
	Prot	Protection degree		IF	20				
	Volta	Voltage			220240 V, 5060 Hz				
	Lifet	Lifetime of LED sources [h]		1	100000				
	Lx/B	у		L	80/B10				
	Ope	rating te	emperature range [°C]	-2	20 ÷ 35				
	Drive	er		S	tandard on/of	f (E)			
	Pow	er facto	r cos φ	>	0,95				
	Circ	uit load	capacity	1	0 (B10), 16 (B	16), 16 (C10), 32	2 (C16)	

Mechanical data Assembly directly mounted to ceiling construction or surface mounted on slings **□ ±**] Material steel sheet В Color RAL 9016 (white) optical system based on PMMA lenses Diffuser IK06 Impact resistant А Dimensions [mm] 900 x 72 x 66

A graph of light

