

## Product: GRANVIA PRO 13000 DOUBLE-ASY-WIDE E 34 840 / L-1500MM Index: 19.4378.3521.34



## Description

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 Im/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

Product information	Category Industrial luminaires		
	Family GRANVIA PRO		
	Name GRANVIA PRO 13000 DOUBLE-ASY-WIDE E 34 840 / L-1500MM		
	Index 19.4378.3521.34		
	$\overbrace{LED} \textcircled{\bullet} \textcircled{\bullet} \textcircled{\bullet} \textcircled{\bullet} \textcircled{\bullet} \textcircled{\bullet} \textcircled{\bullet} $	<b>A</b>	
Light and electrical data	Light source LED		
	Luminous flux LED [lm] 13005,4		
	LED power [W] 62,5		
	Luminaire luminous flux [lm] 11941,6		
	Power of luminaire [W] 70		
	Luminaire's light efficiency [lm/W] 170,6		
	Color of the light [K] 4000		
	CRI >80		
	SDCM (LED sources) 3		
	Beam angle [°] (C0-C180) / (C90-C270) - 95,4° 101,8°	1	
	Photobiological risk class (IEC/EN RG0 62471)		
	Protection against electric shock		
	Protection degree IP20		
	Voltage 220240 V, 5060 Hz		
	Lifetime of LED sources [h] 100000		
	Lx/By <b>L80/B10</b>		
	Operating temperature range [°C] -20 ÷ 35		
	Driver standard on/off (E)		
	Power factor $\cos \varphi$ >0,95		
	Circuit load capacity <b>16 (B10), 26 (B16), 23 (C10), 3</b>	7 (C16	

## **Mechanical data** Assembly directly mounted to ceiling construction or surface mounted on slings **□ ±**] Material steel sheet В Color RAL 9016 (white) optical system based on PMMA lenses Diffuser IK06 Impact resistant А Dimensions [mm] 1500 x 72 x 66

## A graph of light

