

Product: GRANVIA 7500 WIDE E 34 IP54 830 / L-1500MM

Index: 19.4380.4211.34



## **Description**

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 lm/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

## **Product information**

Category	Industrial luminaires
Family	GRANVIA
Name	GRANVIA 7500 WIDE E 34 IP54 830 / L-1500MM
Index	19.4380.4211.34
EAN	5902107605711















## Light and electrical data

Light source	LED
Luminous flux LED [lm]	7379
LED power [W]	35,8
Luminaire luminous flux [lm]	7194,7
Power of luminaire [W]	40,1
Luminaire's light efficiency [lm/W]	179,4
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 79,2° / 77,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP54
Voltage	000 0401/ 50 0011
	220240 V, 5060 Hz
Lifetime of LED sources [h]	90000
	,
Lifetime of LED sources [h]	90000
Lifetime of LED sources [h] Lx/By	90000 L80/B10
Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	90000 L80/B10 -20 ÷ 35



Mechanical data □ ±	Assembly	directly mounted to ceiling construction or surface mounted on slings
В	Material	steel sheet
	Color	RAL 9016 (white)
	Diffuser	optical system based on PMMA lenses
^	Impact resistant	IK06
Α	Dimensions [mm]	1500 x 72 x 66

## A graph of light



