

**Product:** GRANVIA 14500 WIDE EDD 34 IP54 840 / L-2250MM**Index:** 19.4380.4A23.34

## Description

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 lm/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

## Product information

Category	<b>Industrial luminaires</b>
Family	<b>GRANVIA</b>
Name	<b>GRANVIA 14500 WIDE EDD 34 IP54 840 / L-2250MM</b>
Index	<b>19.4380.4A23.34</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>14914,7</b>
LED power [W]	<b>71,3</b>
Luminaire luminous flux [lm]	<b>14542,3</b>
Power of luminaire [W]	<b>79,8</b>
Luminaire's light efficiency [lm/W]	<b>182,2</b>
Color of the light [K]	<b>4000</b>
CRI	<b>&gt;80</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 79,2° / 77,6°</b>
Photobiological risk class (IEC/EN 62471)	<b>RG0</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP54</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>90000</b>
Lx/By	<b>L80/B10</b>
Operating temperature range [°C]	<b>-20 ÷ 35</b>
Driver	<b>DIM DALI (EDD)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>14 (B10), 23 (B16), 22 (C10), 35 (C16)</b>

**Mechanical data**



A

Assembly	<b>directly mounted to ceiling construction or surface mounted on slings</b>
Material	<b>steel sheet</b>
Color	<b>RAL 9016 (white)</b>
Diffuser	<b>optical system based on PMMA lenses</b>
Impact resistant	<b>IK06</b>
Dimensions [mm]	<b>2250 x 72 x 66</b>

**A graph of light**

