

Product: GRANVIA 7500 OVAL E 34 IP54 840 / L-1500MM Index: 19.4380.2221.34




Description

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 Im/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

Product information	CategoryIndustrial luminairesFamilyGRANVIANameGRANVIA 7500 OVAL E 34 IP54 840 / L-1500MMIndex19.4380.2221.34EAN5902107605971
	$\overbrace{LED} \textcircled{\begin{tabular}{c} \hline \end{tabular}} \rule{0.5ex}{1.5ex} \fbox{\begin{tabular}{c} \hline \end{tabular}} \rule{0.5ex}{1.5ex} \fbox{\begin{tabular}{c} \hline \end{tabular}} \rule{0.5ex}{1.5ex} $
Light and electrical data	Light sourceLEDLuminous flux LED [Im]7726,9LED power [W]35,8Luminaire luminous flux [Im]7366,2Power of luminaire [W]40,1Luminaire's light efficiency [Im/W]183,7Color of the light [K]4000CRI>80SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 45,4° / 76,6°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP54Voltage220240 V, 5060 HzLifetime of LED sources [h]90000Lx/ByL80/B10Operating temperature range [°C]-20 ÷ 35Driverstandard on/off (E)Power factor cos φ >0,95Circuit load capacity15 (B10), 25 (B16), 24 (C10), 38 (C16)

Mechanical data directly mounted to ceiling construction or Assembly surface mounted on slings **□ ±**] Material steel sheet В Color RAL 9016 (white) optical system based on PMMA lenses Diffuser Impact resistant IK06 А Dimensions [mm] 1500 x 72 x 66

A graph of light



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025