

Product: GRANVIA PRO 10500 OVAL E 34 IP54 840 / L-1500MM Index: 19.4381.2421.34

- Marine Ma Marine Mari

Description


A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 Im/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

(C16)

Product information	Cate	gory	Industrial luminaires						
	Fam	ily	GRANVIA PRO						
	Nam	е	GRANVIA PRO 10500 OVAL E 34 IP54 840 / L-1500MM						
	Inde	х	19.4381.2421.34						
	EAN		5902107609924						
				E	$\square \square $	IK ₆	Indoor		
Light and electrical data	Ligh	source			LED				
	Lum	Luminous flux LED [Im]			10817				
	LED	LED power [W]			50,8				
	Lum	Luminaire luminous flux [lm]			10312,1				
	Pow	Power of luminaire [W]			56,9				
	Lum	Luminaire's light efficiency [lm/W]			181,2				
	Colo	Color of the light [K]			4000				
	CRI	CRI SDCM (LED sources)			>80				
	SDC				3				
	Bea	Beam angle [°]			(C0-C180) / (C90-C270) - 45,4° / 76,6°				
		Photobiological risk class (IEC/EN 62471)			RG0				
	Prot	Protection against electric shock			I				
	Prot	Protection degree			IP54				
	Volta	Voltage			220240 V, 5060 Hz				
	Lifet	Lifetime of LED sources [h]			100000				
	Lx/B	у			L80/B10				
	Ope	Operating temperature range [°C]			-20 ÷ 35				
	Driv	Driver			standard on/off (E)				
	Pow	Power factor $\cos \phi$			>0,95				
	Circ	Circuit load capacity			15 (B10), 25 (B16), 24 (C10), 38				

Mechanical data directly mounted to ceiling construction or Assembly surface mounted on slings **□ ±**] Material steel sheet В Color RAL 9016 (white) optical system based on PMMA lenses Diffuser Impact resistant IK06 А Dimensions [mm] 1500 x 72 x 66

A graph of light



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025