

Product: GRANVIA PRO 17500 OVAL EDD 34 IP54 840 / L-1500MM Index: 19.4381.2723.34

Junior Marine Marine


Description

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 lm/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

Product information	CategoryIndustrial luminairesFamilyGRANVIA PRONameGRANVIA PRO 17500 OVIndex19.4381.2723.34	AL EDD 34 IP54 840 / L-1500MM
Light and electrical data	Light source Luminous flux LED [Im] LED power [W] Luminaire luminous flux [Im] Power of luminaire [W] Luminaire's light efficiency [Im/W] Color of the light [K] Color of the light [K] CRI SDCM (LED sources) Beam angle [°] Photobiological risk class (IEC/EN 62471) Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C] Driver Power factor cos φ	LED 17891,1 92,8 17056 104 164 4000 >80 3 (C0-C180) / (C90-C270) - 45,4° / 76,6° RG0 I IP54 220240 ∨, 5060 Hz 100000 L80/B10 -20 ÷ 35 DIM DALI (EDD) >0,95
	Circuit load capacity	13 (B10), 21 (B16), 22 (C10), 32 (C16)

Mechanical data directly mounted to ceiling construction or Assembly surface mounted on slings **□ ±**] Material steel sheet В Color RAL 9016 (white) optical system based on PMMA lenses Diffuser Impact resistant IK06 А Dimensions [mm] 1500 x 72 x 66

A graph of light



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025