

Product: GRANVIA PRO 11000 ULTRA-WIDE E 34 IP54 830 / L-2250MM Index: 19.4381.3A11.34

aunum and a state of the state

Description

A cutting-edge energy-efficient linear luminaire, designed to deliver exceptional lighting performance for industrial, warehouse, and commercial spaces. With an impressive luminous efficiency up to 197 Im/W, this advanced lighting system ensures maximum performance while minimizing energy consumption. Installation is tool-less, making the process easy and quick, allowing you to create long lines of light with minimal effort. This luminaire is a perfect solution for supermarkets, large warehouses, and other retail and industrial spaces, offering efficient and sustainable illumination tailored to specific needs. Luminaire is available with 7 different light distributions, IP20 and IP54 version as well as with an option of customised body colour, colour temperature and CRI to match exact needs of most demanding projects.

Product information	CategoryIndustrial luminairesFamilyGRANVIA PRONameGRANVIA PRO 11000 UIndex19.4381.3A11.34EAN5902107610791	ILTRA-WIDE E 34 IP54 830 / L-2250MM
Light and electrical data	Light source Luminous flux LED [lm]	LED 10401,7
	LED power [W]	49,9
	Luminaire luminous flux [lm]	9773
	Power of luminaire [W]	55,9
	Luminaire's light efficiency [lm/W]	174,8
	Color of the light [K]	3000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 99,6° / 96,4°
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	I
	Protection degree	IP54
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000
	Lx/By	L80/B10
	Operating temperature range [°C]	-20 ÷ 35
	Driver	standard on/off (E)
	Power factor $\cos \phi$	>0,95
	Circuit load capacity	11 (B10), 17 (B16), 16 (C10), 27 (C16)

Mechanical data □ [⊥]] ^B	Assembly	directly mounted to ceiling construction or surface mounted on slings
	Material	steel sheet
	Color	RAL 9016 (white)
	Diffuser	optical system based on PMMA lenses
Α	Impact resistant	IK06
	Dimensions [mm]	2250 x 72 x 66

A graph of light



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025