

Product: METEOR LED COMPACT 4000 OPAL E 830 / L-1200

Index: 19.4384.1111.34



Description

Surface mounted luminaires equipped with highly efficient LED sources. Luminaire base made from powder coated steel sheet. Lampshade made from the opal version of methyl polymethacrylate. Luminaire mounted directly on ceilings by raw plugs.

Product information

Category	Compact
Family	METEOR LED COMPACT
Name	METEOR LED COMPACT 4000 OPAL E 830 / L-1200
Index	19.4384.1111.34



Light and electrical data

Light source	LED
Luminous flux LED [lm]	4280,2
LED power [W]	22,2
Luminaire luminous flux [lm]	3430,5
Power of luminaire [W]	24,7
Luminaire's light efficiency [lm/W]	138,9
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 121,6° / 110,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	-20 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	14 (B10), 23 (B16), 22 (C10), 35 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	white
Diffuser	PMMA opal
Impact resistant	IK04
Weight [kg]	2,6
Dimensions [mm]	1255 x 207 x 71

A graph of light

