

Product: METEOR LED COMPACT 4000 OPAL EDD IP44 830 L-1255MM

Index: 19.4384.2113.34



Description

Surface mounted luminaries equipped with highly efficient LED sources. Luminary base made from powder coated steel sheet. Lampshade made from the opal version of methyl polymethacrylate. Luminary mounted directly on ceilings by raw plugs.

Product information

Category	Compact
Family	METEOR LED COMPACT
Name	METEOR LED COMPACT 4000 OPAL EDD IP44 830 L-1255MM
Index	19.4384.2113.34
EAN	5902107617493















Light and electrical data

	. ==
Light source	LED
Luminous flux LED [lm]	4280,2
LED power [W]	22,2
Luminaire luminous flux [lm]	3430,5
Power of luminaire [W]	24,7
Luminaire's light efficiency [lm/W]	138,9
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 121,6° / 110,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	1
Protection against electric shock Protection degree	I IP44
	•
Protection degree	IP44
Protection degree Voltage	IP44 220240 V, 5060 Hz
Protection degree Voltage Lifetime of LED sources [h]	IP44 220240 V, 5060 Hz 100000
Protection degree Voltage Lifetime of LED sources [h] Lx/By	IP44 220240 V, 5060 Hz 100000 L80/B10
Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	IP44 220240 V, 5060 Hz 100000 L80/B10 -20 ÷ 35



		-		
$\mathbf{N}\mathbf{A}\mathbf{A}$	ahr	MIA	\sim 1 \sim	1ata
IVIE			a l ()	lata



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PMMA opal
Impact resistant	IK04
Dimensions [mm]	1255 x 207 x 71

A graph of light





