

Product: AGAT CLEAN CLASS 5-6 NO FRAME LED 2600 SLM EDD IP65 34 830 KRG5DK / 600X300

Index: 19.4386.4113.34



Description

Luminary dedicated for the clean rooms of increased cleanliness class ISO 5-6. Luminary designed to module suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body.

Product information

Category	Clean Class 3-9
Family	AGAT CLEAN CLASS 5-6 NO FRAME LED
Name	AGAT CLEAN CLASS 5-6 NO FRAME LED 2600 SLM EDD IP65 34 830 KRG5DK / 600X300
Index	19.4386.4113.34
EAN	5902107629144
















Light and electrical data

Light source	LED	
Luminous flux LED [lm]	2538	
LED power [W]	12,4	
Luminaire luminous flux [lm]	1830	
Power of luminaire [W]	13,9	
Luminaire's light efficiency [lm/W]	131,7	
Color of the light [K]	3000	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP65	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	100000	
Lx/By	L80/B10	
Operating temperature range [°C]	5 ÷ 30	
Driver	DIM DALI (EDD)	
Power factor cos φ	>0,95	
Circuit load capacity	20 (B10), 31 (B16), 33 (C10), 53 (C16)	



Mechanical data	Assembly	mounted in module ceilings, as well as plasterboard ceilings
	Material	steel sheet
B	Color	RAL 9016 (white)
	Diffuser	SLM (laminated mat glass)
Α	Impact resistant	IK08
	Dimensions [mm]	596 x 296 x 76
	Mounting hole [mm]	580 x 280

A graph of light



Accessories

Index 6BZBO60980

Name Handle for pane opening

