


Product: RUBIN CLEAN-ECO LED 6500 MICRO-PRM SH E IP65 34 830 / 620X620MM**Index:** 19.4387.4511.34

Description

Surface mounted luminary equipped in highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Diffusers permanently mounted, no aluminum frame. Luminary recommended for: emergency departments, intensive care units, and treatment rooms.

Product information

| | |
|----------|---|
| Category | Clean luminaires - surface |
| Family | RUBIN CLEAN-ECO LED |
| Name | RUBIN CLEAN-ECO LED 6500 MICRO-PRM SH E IP65 34 830 / 620X620MM |
| Index | 19.4387.4511.34 |



Light and electrical data

| | |
|---|--|
| Light source | LED |
| Luminous flux LED [lm] | 6345,3 |
| LED power [W] | 31 |
| Luminaire luminous flux [lm] | 4905 |
| Power of luminaire [W] | 34,7 |
| Luminaire's light efficiency [lm/W] | 141,4 |
| Color of the light [K] | 3000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 89° / 89° |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | I |
| Protection degree | IP65 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 100000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | standard on/off (E) |
| Power factor cos φ | 0,95 |
| Circuit load capacity | 25 (B10), 40 (B16), 39 (C10), 62 (C16) |

Mechanical data



| | |
|------------------|--|
| Assembly | surface mounted on ceiling |
| Material | steel sheet |
| Color | RAL 9016 (white) |
| Diffuser | Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass) |
| Impact resistant | IK08 |
| Dimensions [mm] | 620 x 620 x 85 |

A graph of light

