

Product: RUBIN CLEAN-ECO LED 6500 SHM E IP65 34 840 / 620X620MM

Index: 19.4387.3521.34



Description

Surface mounted luminaire equipped in highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Diffusers permanently mounted, no aluminum frame. Luminary recommended for: emergency departments, intensive care units, and treatment rooms.

Product information

Category	Clean luminaires - surface
Family	RUBIN CLEAN-ECO LED
Name	RUBIN CLEAN-ECO LED 6500 SHM E IP65 34 840 / 620X620MM
Index	19.4387.3521.34
EAN	5902107869779



Light and electrical data

Light source	LED
Luminous flux LED [lm]	6679,2
LED power [W]	31
Luminaire luminous flux [lm]	5550
Power of luminaire [W]	34,7
Luminaire's light efficiency [lm/W]	159,9
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	0,95
Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	SHM (hardened mat glass)
Impact resistant	IK08
Dimensions [mm]	620 x 620 x 85

A graph of light

