

**Product:** RUBIN CLEAN-ECO LED 11000 SHM E IP65 34 830 / 620X620MM

**Index:** 19.4387.3611.34



## Description

Surface mounted luminaire equipped in highly efficient LED panels. Luminaire body made from steel sheet, powder coated in white. Diffusers permanently mounted, no aluminum frame. Luminaire recommended for: emergency departments, intensive care units, and treatment rooms.

## Product information

|          |   |
|----------|---|
| Category | Clean luminaires - surface                              |
| Family   | RUBIN CLEAN-ECO LED                                     |
| Name     | RUBIN CLEAN-ECO LED 11000 SHM E IP65 34 830 / 620X620MM |
| Index    | 19.4387.3611.34   |
| EAN      | 5902107869304   |



## Light and electrical data

|   |  |
|---|--|
| Light source                              | LED                                      |
| Luminous flux LED [lm]                    | 11104,2                                  |
| LED power [W]                             | 54,5                                     |
| Luminaire luminous flux [lm]              | 9228                                     |
| Power of luminaire [W]                    | 61                                       |
| Luminaire's light efficiency [lm/W]       | 151,3                                    |
| Color of the light [K]                    | 3000                                     |
| CRI                                       | >80                                      |
| SDCM (LED sources)                        | 3  |
| Beam angle [°]                            | (C0-C180) / (C90-C270) - 109,6° / 109,6° |
| Photobiological risk class (IEC/EN 62471) | RG0                                      |
| Protection against electric shock         | I  |
| Protection degree                         | IP65                                     |
| Voltage                                   | 220..240 V, 50..60 Hz                    |
| Lifetime of LED sources [h]               | 100000                                   |
| Lx/By                                     | L80/B10                                  |
| Operating temperature range [°C]          | 5 ÷ 30                                   |
| Driver                                    | standard on/off (E)                      |
| Power factor cos φ                        | 0,95                                     |
| Circuit load capacity                     | 15 (B10), 25 (B16), 24 (C10), 38 (C16)   |

**Mechanical data**



|                  |                            |
|------------------|----------------------------|
| Assembly         | surface mounted on ceiling |
| Material         | steel sheet                |
| Color            | RAL 9016 (white)           |
| Diffuser         | SHM (hardened mat glass)   |
| Impact resistant | IK08                       |
| Dimensions [mm]  | 620 x 620 x 85             |

**A graph of light**

