

Product: NEPTUN LED V2 7500 PC-OPAL E IP66 21 840 / 1500X92X60MM ZASILANIE PRZELOTOWE 16A

Index: 19.4392.2521.21



Description

Tightly-closed ceiling luminaries with highly efficient LED light sources, ensuring additional protection against solid body penetration and jet of water from all directions. Perfect to be installed in moist and dusty rooms. The luminary is characterized by compact size and unbelievably simple and quick way to install comparing with similar products. The color temperature for applied LED light sources is 3000/4000 K. Color rendering index Ra>80. The luminary is dedicated for rooms with elevated air temperatures. Looping through power supply 16 A.

Product information

| Category | Industrial luminaires |
|----------|---|
| Family | NEPTUN LED V2 |
| Name | NEPTUN LED V2 7500 PC-OPAL E IP66 21 840 / 1500X92X60MM ZASILANIE PRZELOTOWE 16A |
| Index | 19.4392.2521.21 |














Light and electrical data

| Light source | LED |
|--|--|
| Luminous flux LED [lm] | 8402 |
| LED power [W] | 38,6 |
| Luminaire luminous flux [lm] | 6960,3 |
| Power of luminaire [W] | 42,9 |
| Luminaire's light efficiency [lm/W] | 162,2 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 107,2° / 134,4° |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | I |
| | |
| Protection degree | IP66 |
| Protection degree Voltage | IP66 220240 V, 5060 Hz |
| | |
| Voltage | 220240 V, 5060 Hz |
| Voltage Lifetime of LED sources [h] | 220240 V, 5060 Hz 100000 |
| Voltage Lifetime of LED sources [h] Lx/By | 220240 V, 5060 Hz 100000 L80/B10 |
| Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C] | 220240 V, 5060 Hz 100000 L80/B10 -20 ÷ 40 |




Mechanical data



| Assembly | directly mounted to ceiling construction or surface mounted on slings |
|------------------|--|
| Material | polycarbonate |
| Color | RAL 9006 (grey) |
| Diffuser | PC (opalescent polycarbonate) |
| Impact resistant | IK10 |
| Dimensions [mm] | 1500 x 92 x 60 |

A graph of light



Accessories

Index 19.3206.0071.21

Name NEPTUN LED V2 UCHWYT REGULOWANY 21 KPL.

