

## Product: PAREO RETRO LED 9200 STREET-M26 E IP66 04 740 Index: 19.4395.6881.04



## Description

Pareo Retro combines the timeless elegance of historical streetlights with modern LED efficiency, offering superior light quality, energy savings, and sustainability. Perfect for urban roads, parks, and heritage sites, it preserves classic aesthetics while reducing light pollution and operational costs. Durable, versatile, and built to last, Pareo Retro is the ideal choice for eco-friendly, heritage-inspired lighting.

Product information	Category	Outdoor luminaires
	Family	PAREO RETRO LED
	Name Index	PAREO RETRO LED 9200 STREET-M26 E IP66 04 740
		19.4395.6881.04
		$\overbrace{E} \bigoplus \overbrace{E} \bigoplus \biguplus \biguplus \boxtimes \bigotimes \boxtimes \bigotimes$

Light	and	electrical	data
-------	-----	------------	------

electrical data	Light source	LED
	Luminous flux LED [lm]	9566
	LED power [W]	47,2
		,
	Luminaire luminous flux [lm]	6658,4
	Power of luminaire [W]	51,8
	Luminaire's light efficiency [lm/W]	128,5
	Color of the light [K]	4000
	CRI	>70
	SDCM (LED sources)	3
	Beam angle [°]	street light distribution
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	I
	Protection degree	IP66
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	108000
	Lx/By	L95/B10
	Operating temperature range [°C]	-40 ÷ 50
	Driver	standard on/off (E)
	Circuit load capacity	6 (B10), 10 (B16), 10 (C10), 17 (C16)

## **Mechanical data**





Assembly	mounted on poles
Material	aluminum
Color	RAL 9005 (black)
Diffuser	PMMA lenses and hardened transparent glass
Impact resistant	IK09
Dimensions [mm]	400 x 400 x 815

## A graph of light





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025