

# Product: NUMANCIA ARENA LED 1x57000 SUPER-NARROW E IP66 04 740 Index: 19.4399.1381.04

#### Description


Numancia Arena delivers high-efficiency lighting for large-scale outdoor spaces, offering efficiency of up to 196 lm/W. Built for extreme temperatures (-40°C to +40°C) and durable with IP66 and IK09 ratings, it ensures reliable performance in challenging environments. Versatile beam options and high-quality optical systems make it a perfect choice for large sports arenas and other outdoor facilities.

Product information	Category	Outdoor luminaires
	Family	NUMANCIA ARENA LED
	Name	NUMANCIA ARENA LED 1x57000 SUPER-NARROW E IP66 04 740
	Index	19.4399.1381.04
	EAN	5902107640989
		$\overbrace{LED} \textcircled{} \end{array}{} \textcircled{} \end{array}{} \textcircled{} \end{array}{\end{array}}$

### Light and electrical data

Light sourceLEDLuminous flux LED [Im]56583LED power [W]284,1Luminaire luminous flux [Im]52866,1Power of luminaire [W]296,3Luminaire's light efficiency [Im/W]178,4Color of the light [K]4000CRI>70SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 13,6° / 14,4°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP66Voltage220240 V, 5060 HzLifetime of LED sources [h]108000Lx/ByL95/B10Operating temperature range [°C]-40 ÷ 50Driverstandard on/off (E)Circuit load capacity3 (B10), 4 (B16), 4 (C10), 7 (C16)		
LED power [W]284,1Luminaire luminous flux [Im]52866,1Power of luminaire [W]296,3Luminaire's light efficiency [Im/W]178,4Color of the light [K]4000CRI>70SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 13,6° / 14,4°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP66Voltage220240 V, 5060 HzLifetime of LED sources [h]108000Lx/ByL95/B10Operating temperature range [°C]-40 ÷ 50Driverstandard on/off (E)	Light source	LED
Luminaire luminous flux [Im]52866,1Power of luminaire [W]296,3Luminaire's light efficiency [Im/W]178,4Color of the light [K]4000CRI>70SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 13,6° / 14,4°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP66Voltage220.240 V, 5060 HzLifetime of LED sources [h]108000Lx/ByL95/B10Operating temperature range [°C]-40 ÷ 50Driverstandard on/off (E)	Luminous flux LED [lm]	56583
Power of luminaire [W]296,3Luminaire's light efficiency [Im/W]178,4Color of the light [K]4000CRI>70SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 13,6° / 14,4°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP66Voltage220240 V, 5060 HzLifetime of LED sources [h]108000Lx/ByL95/B10Operating temperature range [°C]-40 ÷ 50Driverstandard on/off (E)	LED power [W]	284,1
Luminaire's light efficiency [Im/W]178,4Color of the light [K]4000CRI>70SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 13,6° / 14,4°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP66Voltage220240 V, 5060 HzLifetime of LED sources [h]108000Lx/ByL95/B10Operating temperature range [°C]-40 ÷ 50Driverstandard on/off (E)	Luminaire luminous flux [lm]	52866,1
Color of the light [K]4000CRI>70SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 13,6° / 14,4°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP66Voltage220240 V, 5060 HzLifetime of LED sources [h]108000Lx/ByL95/B10Operating temperature range [°C]-40 ÷ 50Driverstandard on/off (E)	Power of luminaire [W]	296,3
CRI>70SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 13,6° / 14,4°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP66Voltage220240 V, 5060 HzLifetime of LED sources [h]108000Lx/ByL95/B10Operating temperature range [°C]-40 ÷ 50Driverstandard on/off (E)	Luminaire's light efficiency [lm/W]	178,4
SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 13,6° / 14,4°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP66Voltage220240 V, 5060 HzLifetime of LED sources [h]108000Lx/ByL95/B10Operating temperature range [°C]-40 ÷ 50Driverstandard on/off (E)	Color of the light [K]	4000
Beam angle [°](C0-C180) / (C90-C270) - 13,6° / 14,4°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP66Voltage220240 V, 5060 HzLifetime of LED sources [h]108000Lx/ByL95/B10Operating temperature range [°C]-40 ÷ 50Driverstandard on/off (E)	CRI	>70
14,4°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP66Voltage220240 V, 5060 HzLifetime of LED sources [h]108000Lx/ByL95/B10Operating temperature range [°C]-40 ÷ 50Driverstandard on/off (E)	SDCM (LED sources)	3
62471)Protection against electric shockIProtection degreeIP66Voltage220240 V, 5060 HzLifetime of LED sources [h]108000Lx/ByL95/B10Operating temperature range [°C]-40 ÷ 50Driverstandard on/off (E)	Beam angle [°]	
Protection degreeIP66Voltage220240 V, 5060 HzLifetime of LED sources [h]108000Lx/ByL95/B10Operating temperature range [°C]-40 ÷ 50Driverstandard on/off (E)		RG0
Voltage 220240 V, 5060 Hz   Lifetime of LED sources [h] 108000   Lx/By L95/B10   Operating temperature range [°C] -40 ÷ 50   Driver standard on/off (E)	Protection against electric shock	I
Lifetime of LED sources [h]108000Lx/ByL95/B10Operating temperature range [°C]-40 ÷ 50Driverstandard on/off (E)	Protection degree	IP66
Lx/ByL95/B10Operating temperature range [°C]-40 ÷ 50Driverstandard on/off (E)	Voltage	220240 V, 5060 Hz
Operating temperature range [°C]-40 ÷ 50Driverstandard on/off (E)	Lifetime of LED sources [h]	108000
Driver standard on/off (E)	Lx/By	L95/B10
	Operating temperature range [°C]	-40 ÷ 50
Circuit load capacity 3 (B10), 4 (B16), 4 (C10), 7 (C16)	Driver	standard on/off (E)
	Circuit load capacity	3 (B10), 4 (B16), 4 (C10), 7 (C16


#### **Mechanical data**





Assembly	mounted on poles
Material	aluminum
Color	RAL 9005 (black)
Diffuser	PMMA lenses and hardened transparent glass
Impact resistant	IK09
Weight [kg]	13
Dimensions [mm]	768 x 220 x 140

## A graph of light





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025