

Product: NUMANCIA ARENA LED 2x27000 SUPER-NARROW E IP66 04 740 Index: 19.4399.1681.04

Description


Numancia Arena delivers high-efficiency lighting for large-scale outdoor spaces, offering efficiency of up to 196 lm/W. Built for extreme temperatures (-40°C to +40°C) and durable with IP66 and IK09 ratings, it ensures reliable performance in challenging environments. Versatile beam options and high-quality optical systems make it a perfect choice for large sports arenas and other outdoor facilities.

Product information	Category	/ Outdoor luminaires
	Family	NUMANCIA ARENA LED
	Name	NUMANCIA ARENA LED 2x27000 SUPER-NARROW E IP66 04 740
	Index	19.4 <mark>399.16</mark> 81.04
	EAN	5902107641160
		$\overbrace{LED} \textcircled{\begin{tabular}{c}{l}} \textcircled{\begin{tabular}{c}{l}} \\ \hline \end{tabular} \rule{0.5ex}{led} \end{matrix} \rule{0.5ex}{led} 0.$

Light and	electrical	data
-----------	------------	------

Light source Luminous flux LED [Im] LED power [W] Luminaire luminous flux [Im] Power of luminaire [W] Luminaire's light efficiency [Im/W] Color of the light [K] CRI	LED 56520 258 52806,7
LED power [W] Luminaire luminous flux [Im] Power of luminaire [W] Luminaire's light efficiency [Im/W] Color of the light [K] CRI	258 52806,7
Luminaire luminous flux [lm] Power of luminaire [W] Luminaire's light efficiency [lm/W] Color of the light [K] CRI	52806,7
Power of luminaire [W] Luminaire's light efficiency [Im/W] Color of the light [K] CRI	,
Luminaire's light efficiency [lm/W] Color of the light [K] CRI	
Color of the light [K] CRI	269,1
CRI	196,2
	4000
SDCM (LED sourcos)	>70
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 13,6° / 14,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP66
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	108000
Lx/By	L95/B10
Operating temperature range [°C]	-40 ÷ 50
Driver	
Circuit load capacity	standard on/off (E)


Mechanical data





Assembly	mounted on poles
Material	aluminum
Color	RAL 9005 (black)
Diffuser	PMMA lenses and hardened transparent glass
Impact resistant	IK09
Weight [kg]	39
Dimensions [mm]	820 x 455 x 140

A graph of light





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025