

Product: NUMANCIA ARENA LED 2x72000 SUPER-NARROW E IP66 04 740 Index: 19.4399.1981.04

Description

Numancia Arena delivers high-efficiency lighting for large-scale outdoor spaces, offering efficiency of up to 196 lm/W. Built for extreme temperatures (-40°C to +40°C) and durable with IP66 and IK09 ratings, it ensures reliable performance in challenging environments. Versatile beam options and high-quality optical systems make it a perfect choice for large sports arenas and other outdoor facilities.

Product information				
	Category Outdoor luminaires			
		Family NUMANCIA ARENA LED		
	Name NUMANCIA ARENA LED	2x72000 SUPER-NARROW E IP66 04 740		
	Index 19.4399.1981.04			
	CE			
Light and electrical data	Light source	LED		
	Luminous flux LED [lm]	145470		
	LED power [W]	780		
	Luminaire luminous flux [lm]	135917,8		
	Power of luminaire [W]	813,3		
	Luminaire's light efficiency [lm/W]	167,1		
	Color of the light [K]	4000		
	CRI	>70		
	SDCM (LED sources)	3		
	Beam angle [°]	(C0-C180) / (C90-C270) - 13,6° / 14,4°		
	Photobiological risk class (IEC/EN 62471)	RG0		
	Protection against electric shock	I		
	Protection degree	IP66		
	Voltage	220240 V, 5060 Hz		
	Lifetime of LED sources [h]	108000		
	Lx/By	L95/B10		
	Operating temperature range [°C]	-40 ÷ 50		
	Driver	standard on/off (E)		

Circuit load capacity

Mechanical data





Assembly	mounted on poles	
Material	aluminum	
Color	RAL 9005 (black)	
Diffuser	PMMA lenses and hardened transparent glass	
Impact resistant	IK09	
Dimensions [mm]	820 x 455 x 140	

1 (B10), 2 (B16), 1 (C10), 2 (C16)

A graph of light





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025